



INDUCTION TACHOMETERS INDUKTIONSTACHOMETER

Suitable for instant measuring rotation or translation speed. Accurate reading on linear scale. Full scale range: 150 - 3000 r.p.m. Ratio between revolutions and dial indication on request. Dial with double-direction of rotation. Multiple scale dial.

- Black shock-proof plastic body. Protection IP64. Temperature max. 70°C.
- Compensation depending on temperature. Instrument calibration by means of an adjusting screw.
- Drive shaft on self-lubricating bushings, with output at 90°.

Das Gerät zeigt fortwährend die Umdrehungs- und Übertragungsgeschwindigkeit an. Feinablesung auf linear Skala. Skalenbereich zwischen 150 und 3000Rpm. Skalenscheibe mit doppel Umdrehungssinn. Vielfältige Zeigerübersetzungen.

- Gehäuse aus stossfester, selbstlöschender schwarzer Plastik. Schutzart IP64. Maximale Temperatur 70°C,
- Ausgleicheung abhängig von Temperatur. Eichung von Gerät mit Regulierschraube.
- Antriebswelle auf selbstschmierenden Büchsen, Ausgang der Antriebswelle 90°.

TC80 TC100							DRIVE SHAFT POSITION LAGE VON ANTRIEBSWELLEN		DRIVE SHAFT ROTATION WELLENDEHRICHTUNG																											
										1		2																								
Adjusting screw Regulierungsschraube							Drive shaft Antriebswelle			COUPLINGS KUPPLUNGEN																										
										a = $\varnothing 20$		b = M18x1		c = M20x1																						
<table><tr><th>TIPO TYPE</th><th>D</th><th>H</th><th>h</th><th>I</th><th>F</th><th>f</th></tr><tr><td>TC80</td><td>82</td><td>76</td><td>13</td><td>39</td><td>37</td><td>20</td></tr><tr><td>TC100</td><td>106</td><td>83</td><td>15</td><td>39</td><td>37</td><td>20</td></tr></table>							TIPO TYPE	D	H	h	I	F	f	TC80	82	76	13	39	37	20	TC100	106	83	15	39	37	20									
TIPO TYPE	D	H	h	I	F	f																														
TC80	82	76	13	39	37	20																														
TC100	106	83	15	39	37	20																														

PART NR. CONFIGURATION - BESTELLMUSTER

TC80

0-150

DX

C

1

a

VERSION - AUSFÜHRUNGEN

TC80 - TC100

DIAL SCALE - ZIFFERNBLATTSKALA

0-150/0-200/0-300/0-400/0-500/0-600/0-800/0-1000/0-1500/0-2000/0-3000

ROTATION DIRECTION OF DIAL SCALE - ZIFFERNBLATTSKALA DREHRICHTUNG

DX - SX

DRIVE SHAFT POSITION - ANTRIEBSWELLENLAGE

A - B - C - D

DRIVE SHAFT ROTATION DIRECTION - WELLENDEHRICHTUNG

1 = SX; 2 = DX

COUPLINGS - KUPPLUNGEN

1 = SX; 2 = DX